





EURO MTH-16PC



EURO MTH-22PC




EURO MTH-16PC



EURO MTH-22PC


curba de difuziune a luminozității /
крива на разсейване на светлината
 $\eta = 72\%$



C0-C180 C90-C270 [cd/klm]

EURO MTH-250-16PC


curba de difuziune a luminozității /
крива на разсейване на светлината
 $\eta = 73\%$



C0-C180 C90-C270 [cd/klm]

EURO MTH-400-16PC


curba de difuziune a luminozității /
крива на разсейване на светлината
 $\eta = 70\%$



C0-C180 C90-C270 [cd/klm]

EURO MTH-250-22PC

curba de difuziune a luminozității /
крива на разсейване на светлината
 $\eta = 74\%$



C0-C180 C90-C270 [cd/klm]

EURO MTH-400-22PC

- ▶ abajur, geam de protecție: policarbonat (PC) /
instalatie de aprindere: carcasă-aliaj de aluminiu

- ▶ абажур, предпазен екран: поликарбонат (PC) /
пусково устройство: корпус-алуминиева сплав

Kanlux					
EURO MTH-250-16PC	07860	gri / сив	250	2,1	6315
EURO MTH-400-16PC	07861	gri / сив	400	3,5	6690
EURO MTH-250-22PC	07862	gri / сив	250	2,1	7559
EURO MTH-400-22PC	07863	gri / сив	400	3,5	7965

